

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE AUG 1992		2. REPORT TYPE		3. DATES COVERED 00-00-1992 to 00-00-1992	
4. TITLE AND SUBTITLE Safety Considerations in Storing Liquid Gun Propellant XM46				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army ARDEC, ,Picatinny Arsenal,NJ,07806-5000				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES See also ADA261116, Volume IV. Minutes of the Twenty-Fifth Explosives Safety Seminar Held in Anaheim, CA on 18-20 August 1992.					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT Same as Report (SAR)	18. NUMBER OF PAGES 3	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

SAFETY CONSIDERATIONS IN STORING LIQUID GUN PROPELLANT XM46

by J.S. Gardner

U.S. Army ARDEC
Picatinny Arsenal, N.J.
07806-5000

INTRODUCTION

The U.S. Army is currently developing a regenerative liquid propellant gun for artillery application. The liquid propellant XM46 (LP) is composed of 60% Hydroxyl Ammonium Nitrate (HAN), 20% Triethanol Ammonium Nitrate (TEAN), and 20% water. Since this is the first time that a liquid gun propellant is being planned for field use, it is important to investigate the conditions and environment for safely storing the LP. This paper will discuss some of the considerations necessary for storing XM46.

STORAGE COMPATIBILITY GROUP ASSIGNMENT

One major consideration for storing the LP is determined by its storage compatibility group assignment (SCG) given by its hazard classification. Liquid propellants have historically had their own classification and SCG assignment, however these hazard groupings (4 total) are designated by description in DARCOM 385-100 and not by rigorous testing. The LP XM46 is a monopropellant which did not fit any of these liquid hazard groupings. Therefore the tests required for solid propellant classification described in the Army TB 700-2 were modified for liquid propellant testing and then conducted on XM46 (ref 1). These tests resulted in a 1.3 interim hazard classification for the LP, but since there was no designation of liquid propellants for any of the storage compatibility groups in TB 700-2, the XM46 was given a compatibility group C which is the same as that for solid propellants. However, since liquid propellants have never been stored with solid propellants, the safety community requested that compatibility tests be conducted on solid propellants contaminated with XM46. Since there are no formal compatibility tests for an SCG assignment (assignment by description), the tests were developed independantly and then reviewed by the local (ARDEC) Safety Office. The tests were the same as the interim hazard classification tests described in TB 700-2 but were conducted on solid propellants immersed in the LP for at least 3 weeks. These propellants passed all of the tests except for the Thermal Stability test, which indicates that a solid propellant cookoff is possible if contaminated with LP. As a result, the SCG for the LP was changed to group L, which simply states that any material in this group will be stored alone.

The next revision of Army TB 700-2 will be modified for interim hazard classification testing of liquid propellants, but the Storage Compatibility Group descriptions still do not include liquid propellants. It is recommended that a new SCG be developed which is designated specifically for liquid gun propellants, and that formal compatibility tests be developed for assigning new liquid propellants into the appropriate SCG.

MATERIAL COMPATIBILITY

The decomposition temperature of neat XM46 is approximately 125°C, but it can be lowered if it degrades or becomes contaminated. Transition metals, for example, are known to accelerate the decomposition of HAN and lower the decomposition temperature of the LGP. Since the possibility of a spill in the magazine or storage site always exists, it is necessary to determine the compatibility of the LP with anything it may contact. This would include magazine construction materials, pallet and container materials, clothing and cleanup materials. Some of the materials necessary for compatibility tests are given below:

Construction Materials

Concrete
Wood (Softwoods)
Pine
Nails

Packaging Materials

Polyethylene
Low Carbon steel
Paints (MSD 171)
Plastic
Fiberboard

Cleanup Materials

Rags
Rubber gloves
Clothing
Absorbent Mat'ls

The compatibility tests to be developed will require analyzing the integrity of the material after LP contamination and also to analyze the sensitivity of the LP. This is designed to identify any materials which should not contact the LP or to identify the hazards which may occur in case of a spill.

ENVIRONMENTAL PROTECTION

Another important consideration for storing the LP is to protect the environment in the case of a large scale spill. The storage facility may need to be bermed so that any size spill can be contained in the magazine and thereby preventing contamination to the outside environment.

LONG TERM STORAGE

Temperature

It is also necessary to determine the maximum and minimum ambient temperature conditions required for safe long term storage. The XM46 does not freeze above -50 C, which is considered to be the coldest storage condition for propellants, and since degradation is decreased at lower temperatures, it is therefore anticipated that cold temperature storage should be safe.

However, since the LP does decompose more rapidly at elevated temperatures, it is essential to determine the kinetic rates of decomposition as a function of temperature and contamination, and also to determine the ignition temperature of the LP as a function of degradation. Current accelerated aging studies of the LP will eventually answer these questions (ref 2) and their results will be incorporated into the surveillance procedure for monitoring the stability of the LP during long term storage.

Packaging

Another major factor in the long term storage of the LP is its container. It is very important to design a container which is compatible with the LP at the entire storage temperature range of -50°C to 65°C. Since metal contamination can increase LP decomposition, the material in contact with the LP must be non-metallic. However, not all plastic materials are compatible with the LP and other plastics may not maintain its integrity at the required temperature extremes. They may become brittle and break at low temperatures or become soft and pliable at elevated temperature. At the present time, high density polyethylene is the preferred material, but additional compatibility and temperature testing with the LP is required before the final material is chosen.

In addition to the container compatibility, it is also important to incorporate pressure relief features into the container so that any gaseous degradation can be vented thereby avoiding a container explosion from pressure build-up.

REFERENCES

1. Seals, W.O., Herrera, W., and Grelecki, C., Hazard Classification of Liquid Propellants, 1990 JANNAF Propulsion Meeting
2. Tutt, G & Gardner, J.S. , "Modeling the Storage Degradation Kinetics of Liquid Propellant -XM46" 2nd ADPA Predictive Surveillance Symposium, Nov 13-14, 1991